

DS-2CC523P



Key Features

- Compact design
- DIS
- Day/Night with auto switch
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Internal Synchronization
- 3-axis (pan/tilt/rotation) positioning allows adjustment for optimum camera rotation and placement

Specification

Model	DS-2CC523P
Parameter	500 TVL DIS Dome Camera
Camera	
Image Sensor	1/4" DIS
Signal System	PAL/NTSC
Effective Pixels	640 (H) × 480 (V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON) 0.28 Lux @ (F2.0, AGC ON)
Shutter Time	PAL: 1/25 s to 1/15,000 s NTSC: 1/30 s to 1/15,000 s
Lens	3.6 mm @ F2.0 (2.8 mm, 6 mm, 8 mm, 12 mm, 16 mm optional) Angle of view: 54° (3.6 mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 90°, Rotation: 0 - 355°
Day & Night	Electronic
Horizontal Resolution	500 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)

S/N Ratio	More than 52 dB
General	
Operating Conditions	-40 °C - 70 °C (-40 °F - 158 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1 W
Dimension	Φ 97.8 x 64.4 mm (φ 3.85" x 2.54")
Weight	300 g (0.66 lbs)

Dimension

